



Frank O'Bannon
Governor

Lori F. Kaplan
Commissioner

100 North Senate Avenue
P. O. Box 6015
Indianapolis, Indiana 46206-6015
(317) 232-8603
(800) 451-6027
www.state.in.us/idem

FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP) RENEWAL OFFICE OF AIR QUALITY

**Liberty Homes, Inc.
203 South Huntington Street
Syracuse, Indiana 46567**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F085-15189-00043	
Issued by: Original signed by Paul Dubenetzky Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: March 7, 2002 Expiration Date: March 7, 2007

TABLE OF CONTENTS

SECTION A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-8-3(b)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]
- A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]
- A.4 FESOP Applicability [326 IAC 2-8-2]
- A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

SECTION B GENERAL CONDITIONS

- B.1 Permit No Defense [IC 13]
- B.2 Definitions [326 IAC 2-8-1]
- B.3 Permit Term [326 IAC 2-8-4(2)]
- B.4 Enforceability [326 IAC 2-8-6]
- B.5 Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3 (h)]
- B.6 Severability [326 IAC 2-8-4(4)]
- B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]
- B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]
- B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]
- B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]
- B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]
- B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]
- B.13 Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]
- B.14 Emergency Provisions [326 IAC 2-8-12]
- B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]
- B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination
- B.17 Permit Renewal [326 IAC 2-8-3(h)]
- B.18 Permit Amendment or Revision [326 IAC 2-8-10][326 IAC 2-8-11.1]
- B.19 Operational Flexibility [326 IAC 2-8-15]
- B.20 Permit Revision Requirement [326 IAC 2-8-11.1]
- B.21 Inspection and Entry [326 IAC 2-8-5(a)(2)] [I13-14-2-2]
- B.22 Transfer of Ownership or Operation [326 IAC 2-8-10]
- B.23 Annual Fee Payment [326 IAC 2-8-4(6)] [326 IAC 2-8-16]

SECTION C SOURCE OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- C.1 Overall Source Limit [326 IAC 2-8] [326 IAC 2-2]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1][IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Operation of Equipment [326 IAC 2-8-5(a)(4)]
- C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

Testing Requirements [326 IAC 2-8-4(3)]

- C.8 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]

- C.9 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- C.10 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
- C.11 Monitoring Methods [326 IAC 3][40 CFR 60][40 CFR 63]

TABLE OF CONTENTS (Continued)

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]

- C.12 Risk Management Plan [326 IAC 2-8-4] [326 IAC 68.215]
- C.13 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]
- C.14 Actions Related to Noncompliance Demonstrated by a Stack Test

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

- C.15 General Record Keeping Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-5]
- C.16 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]
- C.17 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.1.1 Hazardous Air Pollutants [326 IAC 2-8-4]
- D.1.2 Particulate Matter (PM) from Surface Coating Operations [326 IAC 6-3-2]
- D.1.3 Particulate Matter (PM) from Woodworking Operations [326 IAC 6-3-2]
- D.1.4 Volatile Organic Compounds [326 IAC 2-8-4]
- D.1.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.1.6 HAPs and VOC Emissions
- D.1.7 Volatile Organic Compounds (VOC)
- D.1.8 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- D.1.9 Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

- D.1.10 Visible Emissions Notations
- D.1.11 Cyclone Inspections
- D.1.12 Cyclone Failure Detection

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)][326 IAC 2-8-16]

- D.1.13 Record Keeping Requirements
- D.1.14 Reporting Requirements

Certification Form
Emergency Occurrence Form
Quarterly Report Form
Quarterly Deviation and Compliance Monitoring Report Form

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary modular home manufacturing facility.

Authorized individual:	Michael Nordin
Source Address:	203 South Huntington Street, Syracuse, Indiana 46567
Mailing Address:	P.O. Box 308, Syracuse, Indiana 46567
SIC Code:	2451
Source Location Status:	Kosciusko
County Status:	Attainment for all criteria pollutants
Source Status:	Federally Enforceable State Operating Permit (FESOP)

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

This stationary source consists of the following emission units and pollution control devices:

- (a) One (1) Frame and Floor Fabrication Unit, identified as FFF, consisting of the following:
 - (1) One (1) HVLP spray gun for applying paint to the metal frames.
 - (2) Hand applicators to apply floor sealer and glue to the wooden floor and metal frame.
- (b) One (1) Wall and Cabinet Fabrication Unit, identified as WCF, consisting of the following:
 - (1) Woodworking operations controlled by two (2) cyclone dust collectors, identified as P1 and P2.
 - (2) Three (3) HVLP spray guns for applying adhesives and vapor barrier to the walls and cabinets.
 - (3) Hand applicators to apply miscellaneous glues, sealers, and insulation to the walls and cabinets.
- (c) One (1) Roof Fabrication Unit, identified as RF, consisting of the following:
 - (1) Hand applicators for applying roof cement, roof sealant, and foam sealer.
- (d) One (1) Final Finish and Assembly Unit, identified as FFA, consisting of the following:
 - (1) Hand held aerosol (airless) applicators to apply paint to the finished modular homes.

- (2) Hand applicators to apply adhesives, cleaners and caulk to the finished modular homes.

All HVLP, hand, and aerosol processes exhaust into the interior of the building. The building is exhausted to the outside with a 4,000 scfm wall fan, identified as V1.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion units with heat input equal to or less than ten (10) million Btu per hour.
- (b) A gasoline fuel transfer and dispensing operation handling less than or equal to 1,300 gallons per day, such as filling of tanks, locomotives, automobiles, having a storage capacity less than or equal to 10,500 gallons.
- (c) A petroleum fuel, other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
- (d) Water based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs.
- (e) The following equipment related to manufacturing activities not resulting in the emission of HAPs:
 - (1) Welding operations, located in area FFF, with PM-10 emission less than twenty-five (25) pounds per day:
 - (A) Six (6) stick welders, identified as W1 - W6.
 - (B) Three (3) oxyacetylene torches, identified as T1 - T3.
- (f) Emission units with PM₁₀ and SO₂ emissions less than five (5) pounds per hour or twenty-five (25) pounds per day, CO emissions less than twenty-five (25) pounds per day, and lead emissions less than six-tenths (0.6) tons per year or three and twenty-nine (3.29) pounds per day:
 - (1) One (1) foam pump, identified as FP1.
 - (2) Miscellaneous woodworking equipment located in areas FFF, RF, and FFA.
- (g) Activities and categories of activities with individual HAP emissions not previously identified. Any unit with potential, uncontrolled emissions greater than one (1) pound per day but less than five (5) pound per day or one (1) ton per year of a single HAP.
 - (1) 4, 4' Methylenediphenyl Diisocyanate (MDI) used in polymerization reactions to produce foam insulation. The MDI emissions from this activity are calculated to be 2.5×10^{-6} pounds per hour (0.022 pounds per year).

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ) to renew a Federally Enforceable State Operating Permit (FESOP).

A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

(a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either

- (1) incorporated as originally stated,
- (2) revised, or
- (3) deleted

by this permit.

(b) All previous registrations and permits are superseded by this permit.

SECTION B GENERAL CONDITIONS

B.1 Permit No Defense [IC 13]

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

B.2 Definitions [326 IAC 2-8-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

B.3 Permit Term [326 IAC 2-8-4(2)]

This permit is issued for a fixed term of five (5) years from the original date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.4 Enforceability [326 IAC 2-8-6]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.6 Severability [326 IAC 2-8-4(4)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)] [326 IAC 2-8-5(a)(4)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance

with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). Upon request, the Permittee shall also furnish to IDEM, OAQ, copies of records required to be kept by this permit or, for information claimed to be confidential, the Permittee may furnish such records directly to the U. S. EPA along with a claim of confidentiality.[326 IAC 2-8-4(5)(E)]

- (c) The Permittee may include a claim of confidentiality in accordance with 326 IAC 17. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAQ may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; and
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- (c) An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in condition B, Emergency Provisions.

B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by an authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
 - (5) Such other facts as specified in Sections D of this permit, IDEM, OAQ, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.13 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs), including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

B.14 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ, and Northern Regional Office, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section) or,
Telephone No.: 317-233-5674 (ask for Compliance Section)
Facsimile No.: 317-233-5967

Northern Regional Office
Telephone No.: 1-800-753-5519, or
Telephone No.: 219-245-4870
Facsimile No.: 219-245-4877

Failure to notify IDEM, OAQ and Northern Regional Office, by telephone or facsimile within four (4) daytime business hours after the beginning of the emergency, or after the emergency is discovered or reasonably should have been discovered, shall constitute a violation of 326 IAC 2-8 and any other applicable rules. [326 IAC 2-8-12(f)]

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management

Compliance Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
- (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.
- (g) Operations may continue during an emergency only if the following conditions are met:
 - (1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
 - (2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:
 - (A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and
 - (B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.
- (c) Emergencies shall be included in the Quarterly Deviation and Compliance Monitoring Report.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
- (1) That this permit contains a material mistake.
- (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
- (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAQ, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]

- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.17 Permit Renewal [326 IAC 2-8-3(h)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
 - (2) If IDEM, OAQ upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.
- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]

If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ, any additional information identified as needed to process the application.

B.18 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management

Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.19 Operational Flexibility [326 IAC 2-8-15]

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:

- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
- (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

- (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ, in the notices specified in 326 IAC 2-8-15(b), (c)(1), and (d).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-8-15(a) and the following additional conditions:

- (1) A brief description of the change within the source;
- (2) The date on which the change will occur;
- (3) Any change in emissions; and
- (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

- (c) Emission Trades [326 IAC 2-8-15(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).
- (d) Alternative Operating Scenarios [326 IAC 2-8-15(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAQ or U.S. EPA is required.

B.20 Permit Revision Requirement [326 IAC 2-8-11.1]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-8-11.1.

B.21 Inspection and Entry [326 IAC 2-8-5(a)(2)] [IC 13-14-2-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.22 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-11(b)(3)]

B.23 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-8-4(6)] [326 IAC 2-8-16]

- (a) The Permittee shall pay annual fees to IDEM, OAQ, within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAQ, Technical Support and Modeling Section), to determine the appropriate permit fee.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emissions Limitations and Standards [326 IAC 2-8-4(1)]

C.1 Overall Source Limit [326 IAC 2-8] [326 IAC 2-2]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

- (a) Pursuant to 326 IAC 2-8:
 - (1) The potential to emit any regulated pollutant, except particulate matter (PM), from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.
 - (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
 - (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.
- (b) The potential to emit of particulate matter (PM) from the entire source shall be limited to less than two hundred and fifty (250) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.
- (c) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.
- (d) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

C.6 Operation of Equipment [326 IAC 2-8-5(a)(4)]

Except as otherwise provided by statute, rule or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Quality

100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

Testing Requirements [326 IAC 2-8-4(3)]

C.8 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.10 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented upon issuance of this permit. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

Unless otherwise specified in the approval for the new emissions unit, compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing performed required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63 or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.12 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68; or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and

All documents submitted pursuant to this condition shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

C.13 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and is comprised of:
 - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.

- (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
 - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
 - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
 - (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
 - (4) Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.

- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

**C.14 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]
[326 IAC 2-8-5]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

C.15 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.16 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any quarterly report required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The reports do require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) Reporting periods are based on calendar years.

C.17 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

- (a) One (1) Frame and Floor Fabrication Unit, identified as FFF, consisting of the following:
 - (1) One (1) HVLP spray gun for applying paint to the metal frames.
 - (2) Hand applicators to apply floor sealer and glue to the wooden floor and metal frame.
- (b) One (1) Wall and Cabinet Fabrication Unit, identified as WCF, consisting of the following:
 - (1) Woodworking operations controlled by two (2) cyclone dust collectors, identified as P1 and P2.
 - (2) Three (3) HVLP spray guns for applying adhesives and vapor barrier to the walls and cabinets.
 - (3) Hand applicators to apply miscellaneous glues, sealers, and insulation to the walls and cabinets.
- (c) One (1) Roof Fabrication Unit, identified as RF, consisting of the following:
 - (1) Hand applicators for applying roof cement, roof sealant, and foam sealer.
- (d) One (1) Final Finish and Assembly Unit, identified as FFA, consisting of the following:
 - (1) Hand held aerosol (airless) applicators to apply paint to the finished modular homes.
 - (2) Hand applicators to apply adhesives, cleaners and caulk to the finished modular homes.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.1.1 Hazardous Air Pollutants [326 IAC 2-8-4]

Pursuant to 326 IAC 2-8-4, the hazardous air pollutant emissions shall be limited as follows:

- (a) The amount of any single HAP delivered to the applicator plus the amount of any single HAP used for clean-up shall be limited to 10 tons per twelve (12) consecutive month period.
- (b) The amount of any combination of HAPs delivered to the applicator plus the amount of any combination of HAPs used for clean-up shall not exceed 25 tons per twelve (12) consecutive month period.

Therefore, the requirements of 326 IAC 2-7 do not apply.

D.1.2 Particulate Matter (PM) from Surface Coating Operations [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2(c), the PM from surface coating operations shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
P = process weight rate in tons per hour

D.1.3 Particulate Matter (PM) from woodworking operations [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2, the allowable PM emission rate from the woodworking operations shall not exceed 4.37 pounds per hour when operating at a process weight rate of 2,200 pounds per hour.

The pounds per hour limitation was calculated with the following equation:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

D.1.4 Volatile Organic Compounds [326 IAC 2-8-4]

The potential to emit of VOC from all the surface coating operations is less than 100 tons per year. Therefore, 326 IAC 2-7 does not apply. Any change or modification which may increase the potential emissions to 100 tons per year or more of VOC must be approved by the Office of Air Quality before any such change may occur.

D.1.5 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.1.6 HAPs and VOC Emissions

Compliance with Conditions D.1.1 and D.1.4 shall be demonstrated within 30 days of the end of each month based on the total HAPs and VOC usage for the most recent twelve (12) month period.

D.1.7 Volatile Organic Compounds (VOC)

Compliance with VOC usage limitation contained in Condition D.1.4 shall be determined pursuant to 326 IAC 8-1-4(a)(3) and 326 IAC 8-1-2(a) using formulation data supplied by the coating manufacturer.

D.1.8 Particulate Matter (PM)

Pursuant to permit F085-7685-00043, issued on August 15, 1997, and in order to comply with D.1.3, the cyclones for PM control shall be in operation at all times when the woodworking equipment is in operation.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.1.9 Monitoring

- (a) To document compliance with Condition D.1.2, observations shall be made daily of the overspray while one or more of the spray guns is in operation. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for the specific process. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

D.1.10 Visible Emissions Notations

- (a) Daily visible emission notations of the woodworking stack exhaust shall be performed during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

D.1.11 Cyclone Inspections

An inspection shall be performed each calendar quarter of all cyclones controlling the woodworking operation when venting to the atmosphere. A cyclone inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors.

D.1.12 Cyclone Failure Detection

In the event that cyclone failure has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.1.13 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1 and D.1.4, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the HAPs and VOC usage limits established in Condition D.1.1 and D.1.4.
 - (1) The amount, the HAP content, and the VOC content of each coating material and solvent used. Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used. Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;
 - (2) The cleanup solvent usage for each month;
 - (3) The total HAPs (both single and combined HAPs) and VOC emitted each month; and
 - (4) The weight of HAPs and VOC emitted for each compliance period.
- (b) To document compliance with Condition D.1.2, the Permittee shall maintain a log of daily overspray observations, and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.14 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.1 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
CERTIFICATION**

Source Name: Liberty Homes, Inc.
Source Address: 203 South Huntington Street, Syracuse, Indiana 46567
Mailing Address: P.O. Box 308, Syracuse, Indiana 46567
FESOP No.: F 085-15189-00043

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Affidavit (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE BRANCH
P.O. Box 6015
100 North Senate Avenue
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
EMERGENCY OCCURRENCE REPORT**

Source Name: Liberty Homes, Inc.
Source Address: 203 South Huntington Street, Syracuse, Indiana 46567
Mailing Address: P.O. Box 308, Syracuse, Indiana 46567
FESOP No.: F 085-15189-00043

This form consists of 2 pages

Page 1 of 2

9 This is an emergency as defined in 326 IAC 2-7-1(12)
CThe Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
CThe Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency:

Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency started:
Date/Time Emergency was corrected:
Was the facility being properly operated at the time of the emergency? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____
Title / Position: _____
Date: _____
Phone: _____

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

FESOP Quarterly Report

Source Name: Liberty Homes, Inc.
Source Address: 203 South Huntington Street, Syracuse, Indiana 46567
Mailing Address: P.O. Box 308, Syracuse, Indiana 46567
FESOP No.: F 085-15189-00043
Facility: Frame and Floor Fabrication Unit (FFF), Wall and Cabinet Fabrication Unit (WCF),
Roof Fabrication Unit (RF), and Final Finish and Assembly Unit (FFA).
Parameter: HAPs
Limit: 10 tons per 12 consecutive month period for any single HAP delivered to the entire source.

YEAR: _____

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

FESOP Quarterly Report

Source Name: Liberty Homes, Inc.
Source Address: 203 South Huntington Street, Syracuse, Indiana 46567
Mailing Address: P.O. Box 308, Syracuse, Indiana 46567
FESOP No.: F 085-15189-00043
Facility: Frame and Floor Fabrication Unit (FFF), Wall and Cabinet Fabrication Unit (WCF),
Roof Fabrication Unit (RF), and Final Finish and Assembly Unit (FFA).
Parameter: HAPs
Limit: 25 tons per 12 consecutive month period for any combination of HAPs delivered to
the entire source.

YEAR: _____

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

- 9 No deviation occurred in this quarter.
- 9 Deviation/s occurred in this quarter.
Deviation has been reported on: _____

Submitted by: _____
Title / Position: _____
Signature: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR QUALITY
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT**

Source Name: Liberty Homes, Inc.
Source Address: 203 South Huntington Street, Syracuse, Indiana 46567
Mailing Address: P.O. Box 308, Syracuse, Indiana 46567
FESOP No.: F 085-15189-00043

Months: _____ to _____ Year: _____

Page 1 of 2

This report is an affirmation that the source has met all the requirements stated in this permit. This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)

Date of Deviation:

Duration of Deviation:

Number of Deviations:

Probable Cause of Deviation:

Response Steps Taken:

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Permit Requirement (specify permit condition #)	
Date of Deviation:	Duration of Deviation:
Number of Deviations:	
Probable Cause of Deviation:	
Response Steps Taken:	

Form Completed By: _____

Title/Position: _____

Date: _____

Phone: _____

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Addendum to the Technical Support Document for Federally Enforceable State Operating Permit (FESOP) Renewal

Source Background and Description

Source Name: Liberty Homes, Inc.
Source Location: 203 S. Huntington Street, Syracuse, Indiana 46567
County: Kosciusko
SIC Code: 2451
Operation Permit No.: F085-15189-00043
Permit Reviewer: ERG/YC

On January 29, 2002, the Office of Air Quality (OAQ) had a notice published in the Times Union, Warsaw, Indiana, stating that Liberty Homes, Inc. had applied for a Federally Enforceable State Operating Permit (FESOP) Renewal to operate a modular home manufacturing facility with control. The notice also stated that OAQ proposed to issue a permit for this operation and provided information on how the public could review the proposed permit and other documentation. Finally, the notice informed interested parties that there was a period of thirty (30) days to provide comments on whether or not this permit should be issued as proposed.

Upon further review, the OAQ has decided to make the following revisions to the permit (bolded language has been added, the language with a line through it has been deleted). The Table Of Contents has been modified to reflect these changes.

1. Condition A.5, Prior Permit Conditions has been replaced by the new Condition A.5, Prior Permits Superseded, which helps to clarify the intent of the new rule 326 IAC 2-1.1-9.5.

~~A.5 Prior Permit Conditions~~

- ~~(a) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits.~~
- ~~(b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAQ, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued.~~

A.5 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either**
 - (1) incorporated as originally stated,**
 - (2) revised, or**
 - (3) deleted**

by this permit.

(b) All previous registrations and permits are superseded by this permit.

2. The IDEM, OAQ, has corrected Condition B.15 Deviations from Permit Requirements and Conditions by adding the word not to the sentence, " A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit shall be reported according to the schedule stated in the applicable requirement and does need to be included in this report."

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

- (a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Quality
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit shall be reported according to the schedule stated in the applicable requirement and does **not** need to be included in this report.

3. The title Compliance Response Plan - Failure to Take Response Steps has been corrected to Compliance Response Plan - Preparation, Implementation, Records, and Reports in Conditions C.13, D.1.9, D.10, and D.12.

C.13 Compliance Response Plan - ~~Failure to Take Response Steps~~ Preparation, Implementation, Records, and Reports [326 IAC 2-8-4] [326 IAC 2-8-5]

D.1.9 Monitoring

- (a) To document compliance with Condition D.1.2, observations shall be made daily of the overspray while one or more of the spray guns is in operation. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for the specific process. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Response Plan - ~~Failure to Take Response Steps~~ **Preparation, Implementation, Records, and Reports**, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C - Compliance Response Plan - ~~Failure to Take Response Steps~~ **Preparation, Implementation, Records, and Reports**, shall be considered a violation of this permit.

D.1.10 Visible Emissions Notations

- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - ~~Failure to Take Response Steps~~ **Preparation, Implementation, Records, and Reports**, shall be considered a violation of this permit.

D.1.12 Cyclone Failure Detection

In the event that cyclone failure has been observed:

Failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). Failure to take response steps in accordance with Section C - Compliance Response Plan - ~~Failure to Take Response Steps~~ **Preparation, Implementation, Records, and Reports**, shall be considered a violation of this permit.

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Federally Enforceable Operating Permit (FESOP) Renewal

Source Background and Description

Source Name: Liberty Homes, Inc.
Source Location: 203 S. Huntington Street, Syracuse, Indiana 46567
County: Kosciusko
SIC Code: 2451
Operation Permit No.: F085-15189-00043
Permit Reviewer: ERG/YC

The Office of Air Quality (OAQ) has reviewed a FESOP renewal application from Liberty Homes, Inc. relating to the operation of a modular home manufacturing facility. Liberty Homes, Inc. was issued FESOP 085-7685-0043 on August 15, 1997.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

- (a) One (1) Frame and Floor Fabrication Unit, identified as FFF, consisting of the following:
 - (1) One (1) HVLP spray gun for applying paint to the metal frames.
 - (2) Hand applicators to apply floor sealer and glue to the wooden floor and metal frame.
- (b) One (1) Wall and Cabinet Fabrication Unit, identified as WCF, consisting of the following:
 - (1) Woodworking operations controlled by two (2) cyclone dust collectors, identified as P1 and P2.
 - (2) Three (3) HVLP spray guns for applying adhesives and vapor barrier to the walls and cabinets.
 - (3) Hand applicators to apply miscellaneous glues, sealers, and insulation to the walls and cabinets.
- (c) One (1) Roof Fabrication Unit, identified as RF, consisting of the following:
 - (1) Hand applicators for applying roof cement, roof sealant, and foam sealer.
- (d) One (1) Final Finish and Assembly Unit, identified as FFA, consisting of the following:

- (1) Hand held aerosol (airless) applicators to apply paint to the finished modular homes.
- (2) Hand applicators to apply adhesives, cleaners and caulk to the finished modular homes.

All HVLP, hand, and aerosol processes exhaust into the interior of the building. The building is exhausted to the outside with a 4,000 scfm wall fan, identified as V1.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities operating at this source during this review process.

New Emission Units and Pollution Control Equipment Receiving New Source Review Approval

There are no new emission units and pollution control equipment proposed during this review process.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Natural gas-fired combustion units with heat input equal to or less than ten (10) million Btu per hour.
- (b) A gasoline fuel transfer and dispensing operation handling less than or equal to 1,300 gallons per day, such as filling of tanks, locomotives, automobiles, having a storage capacity less than or equal to 10,500 gallons.
- (c) A petroleum fuel, other than gasoline, dispensing facility, having a storage capacity of less than or equal to 10,500 gallons, and dispensing less than or equal to 230,000 gallons per month.
- (d) Water based adhesives that are less than or equal to 5% by volume of VOCs excluding HAPs.
- (e) The following equipment related to manufacturing activities not resulting in the emission of HAPs:
 - (1) Welding operations, located in area FFF, with PM-10 emission less than twenty-five (25) pounds per day:
 - (A) Six (6) stick welders, identified as W1 - W6.
 - (B) Three (3) oxyacetylene torches, identified as T1 - T3.
- (f) Emission units with PM₁₀ and SO₂ emissions less than five (5) pounds per hour or twenty-five (25) pounds per day, CO emissions less than twenty-five (25) pounds per day, and lead emissions less than six-tenths (0.6) tons per year or three and twenty-nine (3.29) pounds per day:
 - (1) One (1) foam pump, identified as FP1.
 - (2) Miscellaneous woodworking equipment located in areas FFF, RF, and FFA.

- (g) Activities and categories of activities with individual HAP emissions not previously identified. Any unit with potential, uncontrolled emissions greater than one (1) pound per day but less than five (5) pound per day or one (1) ton per year of a single HAP.
- (1) 4, 4' Methylenediphenyl Diisocyanate (MDI) used in polymerization reactions to produce foam insulation. The MDI emissions from this activity are calculated to be 2.5×10^{-6} pounds per hour (0.022 pounds per year).

Existing Approvals

- (a) FESOP 085-7685-00043, issued on August 15, 1997; and expires on August 15, 2002, and

All conditions from previous approvals were incorporated into this FESOP.

However, the frequency of the visible emissions notations for woodworking operations has been changed from once per shift to daily.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the FESOP Renewal be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

There was no notice of completeness letter mailed to the source.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (Pages 1 through 9).

Unrestricted Potential Emissions

This table reflects the unrestricted potential emissions of the source, excluding the emission limits that were contained in the previous FESOP.

Pollutant	Unrestricted Potential Emissions (tons/yr)
PM	78.36
PM-10	78.36
SO ₂	--
VOC	66.99
CO	--
NO _x	--

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Unrestricted Potential Emissions (tons/yr)
Vinyl Acetate	0.07
Glycol Ethers	0.18
Hexane	4.52

HAP's	Unrestricted Potential Emissions (tons/yr)
Toluene	0.75
Ethyene Glycol	32.54
Mathylene Chloride	2.93
Xylene	1.12
Methylethyl Ketone	7.27
TOTAL	49.39

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of any single HAP is equal to or greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-1.1-1(16)) of a combination HAPs is greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) Fugitive Emissions
Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are no applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive emissions are not counted toward determination of PSD and Emission Offset applicability.

Potential to Emit After Issuance

The source, issued a FESOP on August 15 1997, has opted to remain a FESOP source, rather than apply for a Part 70 Operating Permit. The table below summarizes the potential to emit, reflecting all limits, of the emission units. Any control equipment is considered enforceable only after issuance of this Federally Enforceable State Operating Permit and only to the extent that the effect of the control equipment is made practically enforceable in the permit. Since the source has not constructed any new emission units, the source's potential to emit is based on the emission units included in the original FESOP. (F085-7685-00043; issued on August 15, 1997).

Process/emission unit	Potential to Emit After Issuance (tons/year)						HAPs
	PM	PM-10	SO ₂	VOC	CO	NO _x	
Frame and Floor Fabrication Unit (FFF)	2.35	2.35	--	0.60	--	--	Less than 10 for single HAP and 25 for combination HAPs
Wall and Cabinet Fabrication Unit (WCF)	41.24	41.24	--	42.24	--	--	
Roof Fabrication Unit (RF)	--	--	--	14.30	--	--	
Final Finish and Assembly Unit (FFA)	0.11	0.11	--	9.85	--	--	
Total PTE After Issuance	43.71	43.71	--	66.99	--	--	Less than 10 for single HAP and 25 for combination HAPs

County Attainment Status

The source is located in Kosciusko County.

Pollutant	Status
PM-10	Attainment
SO ₂	Attainment
NO ₂	Attainment
Ozone	Attainment
CO	Attainment
Lead	Attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Kosciusko County has been designated as attainment or unclassifiable for ozone.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source.

State Rule Applicability - Entire Source

326 IAC 2-6 (Emission Reporting)

This source is located in Kosciusko County and the potential to emit all criteria pollutants is less than one hundred (100) tons per year. Therefore, 326 IAC 2-6 does not apply.

326 IAC 2-8-4 (FESOP)

The potential HAP emissions from the entire source is more than 10 tons per year for a single HAP and 25 tons per year for a combination of HAPs. Pursuant to 326 IAC 2-8-4, the hazardous air pollutant emissions shall be limited as follows:

- (a) The amount of any single HAP delivered to the applicator plus the amount of any single HAP used for clean-up shall be limited to 10 tons per twelve (12) consecutive month period.
- (b) The amount of any combination of HAPs delivered to the applicator plus the amount of any combination of HAPs used for clean-up shall not exceed 25 tons per twelve (12) consecutive month period.

Therefore, the requirements of 326 IAC 2-7 do not apply.

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A,

Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 8-2 (Surface Coating Emission Limitations)

All the facilities in this source were constructed before January 1, 1980 and is located in Kosciusko county. Therefore, rule 326 IAC 8-2 does not apply to this facility.

326 IAC 8-1-6 (General Reduction Requirements for VOC Emissions)

All the facilities in this source were constructed before January 1, 1980. Therefore, rule 326 IAC 8-1-6 does not apply to this facility.

326 IAC 8-6 (Organic Solvent Emission Limitations)

Since the source has been in operation since before October 7, 1974 and the potential emissions of VOC are less than 100 tons per year, 326 IAC 8-6 does not apply.

326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the surface coating operations shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

326 IAC 6-3-2 (Process Operations)

The allowable PM emission rate from the woodworking operations shall be limited to 4.37 pounds per hour for a maximum process weight rate of 2,200 pounds per hour.

This limitation is based on the following equation:

$$P_t = 4.10 P^{0.67}$$

where E = rate of emission in pounds per hour; and
 P = process weight rate in tons per hour

In order to meet the emission limit of 4.37 lbs/hr, the cyclones shall be in operation at all times the woodworking equipment is in operation.

Testing Requirements

No testing requirements exists in the previous FESOP and this FESOP, since the compliance methods are based on mass balance and recordkeeping.

Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as

grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The following new compliance requirements were incorporated into this FESOP:

1. Woodworking operations have the applicable monitoring conditions as specified below:
 - (a) An inspection shall be performed each calendar quarter of all cyclones controlling the woodworking operation when venting to the atmosphere. A cyclone inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting to the indoors.
 - (b) In the event that cyclone failure has been observed, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit.

These conditions are necessary because the cyclones for the woodworking process must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) and 326 IAC 2-8 (FESOP).

All compliance requirements from previous approvals were incorporated into this FESOP. The source is also subject to the following compliance monitoring requirements:

1. The surface coating operations (all units) have the applicable monitoring condition as specified below:
 - (a) Observations shall be made daily of the overspray while one or more of the booths is in operation. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for the specific process. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step.
 - (b) Weekly inspections shall be performed of the coating emissions from the stack and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step.

These monitoring conditions are necessary because the system coating operations must be in compliance with 326 IAC 6-3 (Process Operations).

2. The woodworking operations (unit WCF) have the applicable monitoring condition as specified below:

Daily visible emissions notations of the stack exhaust from the woodworking operations shall be performed at least during normal daylight operations. A trained employee will

record whether emissions are normal or abnormal. For processes operated continuously "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

This condition is necessary to ensure the woodworking operations are in compliance with 326 IAC 6-3 (Process Operations).

Conclusion

The operation of this modular home manufacturing facility shall be subject to the conditions of the attached proposed (FESOP No.: F085-15189-00043).

**Appendix A: Emissions Calculations
VOC and Particulate
From the Frame and Floor Fabrication Unit (FFF)**

Page 1 of 9 TSD App A

**Company Name: Liberty Home, Inc.
Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567
FESOP: F085-15189-00043
Reviewer: ERG/YC
Date: December 5, 2001**

Material	Density (Lb/Gal)	Weight % Volatile (H ₂ O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating	Potential VOC (lbs/hr)	Potential VOC (lbs/day)	Potential VOC (tons/yr)	PM Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
Frame Paint	8.59	75.00%	72.0%	3.0%	74.0%	22.00%	0.574	0.87	0.26	0.13	3.09	0.56	2.35	1.17	50%
Floor Seaier	8.76	45.00%	45.0%	0.0%	50.0%	50.00%	0.364	0.87	0.00	0.00	0.00	0.00	0.00	0.00	100%
Glue	9.10	60.10%	60.0%	0.1%	65.0%	35.00%	1.035	0.87	0.01	0.01	0.20	0.04	0.00	0.03	100%

												VOC	PM		
State Potential Emissions								Totals	0.14	3.29	0.60	2.35			

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)
Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)
Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)
Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)
Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)
Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)
Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)
Total = Worst Coating + Sum of all solvents used

Appendix A: Emissions Calculations

HAPs

From the Frame and Floor Fabrication Unit (FFF)

Company Name: Liberty Home, Inc.
Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567
FESOP: F085-15189-00043
Reviewer: ERG/YC
Date: December 5, 2001

Material	Density (Lb/Gal)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Weight % Vinyl Acetate	Vinyl Acetate Emissions (tons/yr)	Weight % Glycol Ethers	Glycol Ethers Emissions (tons/yr)	Weight % Hexane	Hexane Emissions (tons/yr)	Weight % Toluene	Toluene Emissions (tons/yr)	Weight % Ethyene Glycol	Ethyene Glycol Emissions (tons/yr)	Weight % Methylene Chloride	Methylene Chloride Emissions (tons/yr)	Weight % Xylene	Xylene Emissions (tons/yr)	Weight % Methylethyl Ketone	Methylethyl Ketone Emissions (tons/yr)
Frame Paint	8.59	0.574	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Floor Sealer	8.76	0.364	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Glue	9.10	1.035	0.87	0.10%	0.04	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00

	Vinyl Acetate	Glycol Ethers	Hexane	Toluene	Ethyene Glycol	Methylene Chloride	Xylene	Methylethyl Ketone
Total State Potential Emissions (Single HAP)	0.04	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total Combination of HAPs	0.04							

METHODOLOGY

HAPs emission rate (tons/yr) = Density (lb/gal) x Gal of Material (gal/unit) x Maximum (unit/hr) x Weight % HAP x 8760 hr/yr x 1 ton/2000 lbs

Appendix A: Emissions Calculations

VOC and Particulate

From the Coating Process of the Wall and Cabinet Fabrication Unit (WCF)

Company Name: Liberty Home, Inc.

Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567

FESOP: F085-15189-00043

Reviewer: ERG/YC

Date: December 5, 2001

Material	Density (Lb/Gal)	Weight % Volatile (H ₂ O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating	Potential VOC (lbs/hr)	Potential VOC (lbs/day)	Potential VOC (tons/yr)	PM Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
Ever Foam	10.01	54.80%	25.0%	29.8%	22.0%	47.0%	0.356	0.87	2.98	0.92	22.17	4.05	0.00	6.35	100%
MH9000	8.82	36.40%	1.4%	35.0%	1.9%	46.2%	0.448	0.87	3.09	1.20	28.88	5.27	0.00	6.68	100%
Glue	9.10	60.10%	60.0%	0.1%	65.0%	35.0%	1.035	0.87	0.01	0.01	0.20	0.04	0.00	0.03	100%
Stix 309	8.00	40.50%	40.0%	0.5%	38.0%	62.0%	0.421	0.87	0.04	0.01	0.35	0.06	3.82	0.06	50%
Vapor Barrier	10.01	30.50%	0.0%	30.5%	0.0%	65.0%	2.797	0.87	3.05	7.43	178.30	32.54	37.07	4.70	50%
Silicone	6.67	5.00%	0.0%	5.0%	0.0%	93.0%	0.225	0.87	0.33	0.07	1.57	0.29	0.00	0.36	100%
Joint Compound	10.30	20.20%	20.2%	0.0%	25.0%	75.0%	2.900	0.87	0.00	0.00	0.00	0.00	0.00	0.00	100%

										VOC	PM
State Potential Emissions										Totals	40.89
										9.64	231.47
										42.24	40.89

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) * (8760 hrs/yr) * (1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

Appendix A: Emissions Calculations

HAPs

From the Coating Process of the Wall and Cabinet Fabrication Unit (WCF)

Company Name: Liberty Home, Inc.

Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567

FESOP: F085-15189-00043

Reviewer: ERG/YC

Date: December 5, 2001

Material	Density (Lb/Gal)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Weight % Vinyl Acetate	Vinyl Acetate Emissions (tons/yr)	Weight % Glycol Ethers	Glycol Ethers Emissions (tons/yr)	Weight % Hexane	Hexane Emissions (tons/yr)	Weight % Toluene	Toluene Emissions (tons/yr)	Weight % Ethylene Glycol	Ethylene Glycol Emissions (tons/yr)	Weight % Methylene Chloride	Methylene Chloride Emissions (tons/yr)	Weight % Xylene	Xylene Emissions (tons/yr)	Weight % Methyl ethyl Ketone	Methyl ethyl Ketone Emissions (tons/yr)
Ever Foam	10.01	0.356	0.87	0.00%	0.00	1.30%	0.18	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.50%	0.07	0.00%	0.00	0.00%	0.00
MH9000	8.82	0.448	0.87	0.00%	0.00	0.00%	0.00	30.00%	4.52	5.00%	0.75	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Glue	9.10	1.035	0.87	0.10%	0.04	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Stix 309	8.00	0.421	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Vapor Barrier	10.01	2.797	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	30.50%	32.54	0.00%	0.00	0.00%	0.00	0.00%	0.00
Silicone	6.67	0.225	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Joint Compound	10.30	2.900	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00

	Vinyl Acetate	Glycol Ethers	Hexane	Toluene	Ethylene Glycol	Methylene Chloride	Xylene	Methyl ethyl Ketone
Total State Potential Emissions (Single HAP)	0.04	0.18	4.52	0.75	32.54	0.07	0.00	0.00
Total Combination of HAPs	38.09							

METHODOLOGY

HAPs emission rate (tons/yr) = Density (lb/gal) x Gal of Material (gal/unit) x Maximum (unit/hr) x Weight % HAP x 8760 hr/yr x 1 ton/2000 lbs

Appendix A: Emissions Calculations

Page 5 of 9 TSD App A

Particulate Emissions

From the woodworking process of the Wall and Cabinet Fabrication Unit (WCF)

Company Name: Liberty Home, Inc.

Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567

FESOP: F085-15189-00043

Reviewer: ERG/YC

Date: December 18, 2001

Woodworking Process Discription:

Throughput of Wood: 2200 lbs/hr
PM Control Euipment: Dust Collector - Cyclone
Grain Loading: 0.00078 grains/acf
Air Flow Rate: 12000 acf/m
Control Efficiency: 99.00%

After Control Emissions:

Hourly PM Emissions	= 0.0078 (gr/acf) x 12000 (acf/min) x 60 (min/hr) x 1/7000 (lb/gr) =	0.08 lbs/hr
Annual PM emissions	= 0.08 lbs/hr x 8760 hr/yr x 1/2000 (ton/lb) =	0.35 tons/yr

Before Control Emissions:

Potential PM emissions	= 0.35 tons/yr / (1-99%) =	35 tons/yr
-------------------------------	----------------------------	-------------------

**Appendix A: Emissions Calculations
VOC and Particulate
From the Roof Fabrication Unit (RF)**

Page 6 of 9 TSD App A

**Company Name: Liberty Home, Inc.
Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567
FESOP: F085-15189-00043
Reviewer: ERG/YC
Date: December 5, 2001**

Material	Density (Lb/Gal)	Weight % Volatile (H ₂ O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating	Potential VOC (lbs/hr)	Potential VOC (lbs/day)	Potential VOC (tons/yr)	PM Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
Roof Cement	8.34	23.70%	0.0%	23.7%	0.0%	70.0%	1.720	0.87	1.98	2.96	70.99	12.95	0.00	2.82	100%
Roof Sealant	8.34	23.70%	0.0%	23.7%	0.0%	70.0%	0.178	0.87	1.98	0.31	7.35	1.34	0.00	2.82	100%
Foam Seal	9.51	0.00%	0.0%	0.0%	0.0%	100.0%	2.400	0.87	0.00	0.00	0.00	0.00	0.00	0.00	100%

State Potential Emissions	Totals	3.26	78.33	VOC 14.30	PM 0.00
----------------------------------	---------------	-------------	--------------	----------------------	--------------------

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

Appendix A: Emissions Calculations

HAPs

From the Roof Fabrication Unit (RF)

Company Name: Liberty Home, Inc.
Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567
FESOP: F085-15189-00043
Reviewer: ERG/YC
Date: December 5, 2001

Material	Density (Lb/Gal)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Weight % Vinyl Acetate	Vinyl Acetate Emissions (tons/yr)	Weight % Glycol Ethers	Glycol Ethers Emissions (tons/yr)	Weight % Hexane	Hexane Emissions (tons/yr)	Weight % Toluene	Toluene Emissions (tons/yr)	Weight % Ethylene Glycol	Ethylene Glycol Emissions (tons/yr)	Weight % Methylene Chloride	Methylene Chloride Emissions (tons/yr)	Weight % Xylene	Xylene Emissions (tons/yr)	Weight % Methylethyl Ketone	Methylethyl Ketone Emissions (tons/yr)
Roof Cement	8.34	1.720	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Roof Sealant	8.34	0.178	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00
Foam Seal	9.51	2.400	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00

	Vinyl Acetate	Glycol Ethers	Hexane	Toluene	Ethylene Glycol	Methylene Chloride	Xylene	Methylethyl Ketone
Total State Potential Emissions (Single HAP)	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total Combination of HAPs	0.00							

METHODOLOGY

HAPs emission rate (tons/yr) = Density (lb/gal) x Gal of Material (gal/unit) x Maximum (unit/hr) x Weight % HAP x 8760 hr/yr x 1 ton/2000 lbs

Appendix A: Emissions Calculations
VOC and Particulate
From the Final Finish and Assembly Unit (WCF)

Page 8 of 9 TSD App A

Company Name: Liberty Home, Inc.
Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567
FESOP: F085-15189-00043
Reviewer: ERG/YC
Date: December 5, 2001

Material	Density (Lb/Gal)	Weight % Volatile (H ₂ O & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating	Potential VOC (lbs/hr)	Potential VOC (lbs/day)	Potential VOC (tons/yr)	PM Potential (ton/yr)	lb VOC/gal solids	Transfer Efficiency
Adhesive	7.09	70.00%	0.0%	70.0%	0.0%	20.8%	0.200	0.87	4.96	0.86	20.73	3.78	0.00	23.86	100%
Cleaner	6.61	100.00%	10.0%	90.0%	10.0%	0.0%	0.154	0.87	5.95	0.80	19.13	3.49	0.00	-	100%
Piant	7.80	95.00%	63.0%	32.0%	45.0%	8.0%	0.153	0.87	2.50	0.33	7.97	1.46	0.11	31.20	50%
Caulk	8.17	40.00%	0.0%	40.0%	0.0%	75.0%	0.090	0.87	3.27	0.26	6.14	1.12	0.00	4.36	100%

												VOC	PM		
State Potential Emissions								Totals	2.25	53.97	9.85	0.11			

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

Appendix A: Emissions Calculations

HAPs

From the Final Finish and Assembly Unit (WCF)

Company Name: Liberty Home, Inc.
Address City IN Zip: 203 S. Huntington Street, Syracuse, IN 46567
FESOP: F085-15189-00043
Reviewer: ERG/YC
Date: December 5, 2001

Material	Density (Lb/Gal)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Weight % Vinyl Acetate	Vinyl Acetate Emissions (tons/yr)	Weight % Glycol Ethers	Glycol Ethers Emissions (tons/yr)	Weight % Hexane	Hexane Emissions (tons/yr)	Weight % Toluene	Toluene Emissions (tons/yr)	Weight % Ethylene Glycol	Ethylene Glycol Emissions (tons/yr)	Weight % Methylene Chloride	Methylene Chloride Emissions (tons/yr)	Weight % Xylene	Xylene Emissions (tons/yr)	Weight % Methylene Ketone	Methylene Ketone Emissions (tons/yr)
Adhesive	7.09	0.200	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	70.00%	3.78
Cleaner	6.61	0.154	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	90.00%	3.49
Plant	7.80	0.153	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	63.00%	2.86	0.00%	0.00	0.00%	0.00
Caulk	8.17	0.090	0.87	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	0.00%	0.00	40.00%	1.12	0.00%	0.00

	Vinyl Acetate	Glycol Ethers	Hexane	Toluene	Ethylene Glycol	Methylene Chloride	Xylene	Methylene Ketone
Total State Potential Emissions (Single HAP)	0.00	0.00	0.00	0.00	0.00	2.86	1.12	7.27
Total Combination of HAPs	11.26							

METHODOLOGY

HAPs emission rate (tons/yr) = Density (lb/gal) x Gal of Material (gal/unit) x Maximum (unit/hr) x Weight % HAP x 8760 hr/yr x 1 ton/2000 lbs